MicroCoMPASS™

Micro Compact Multi-Purpose Advanced Stabilized System – UAV

General

The MicroCoMPASS is the latest member of the battle-proven CoMPASS stabilized EO payload family, in use worldwide.

Features:

- Ultra-lightweight, extremely compact design, high stabilization level optimized for installation on unmanned platforms
- Cutting-edge electro-optical technology, delivering superb continuous zoom night and day observation and surveillance capabilities
- Single LRU integrating four EO elements: large-format continuous zoom thermal imager, zoom color TV camera with low light mode, eyesafe laser rangefinder (ELRF) and laser target illuminator
- Equipped with 3 gimbals which provide the MicroCoMPASSTM high stabilization level

Elbit Systems™ ISTAR & EW

MicroCoMPASS

Micro Compact Multi-Purpose Advanced Stabilized System – UAV

Applications

- Surveillance and reconnaissance
- Force and convoy protection
- Shipboard operation capability
- Border and coastal surveillance
- Law enforcement
- Strategic infrastructure security

Main Advantages & Features

- Stabilized real-time video
- Long-range continuous zoom thermal imager and zoom color CCD camera
- Automatic tracking of observed targets
- Lightweight, compact design with low power consumption
- Simple and straightforward installation utilizing single LRU configuration and minimum cabling

Technical Data

System

• Diameter	8.2"
• Weight	<9 Kg
• Angular coverage	
- Azimuth	N x 360°
- Elevation	+30° to -85°
• Environmental conditions	MIL-STD-810F
• Video output standard	PAL, NTSC

Thermal Imager

• FLIR	Cooled 3rd generation 3-5µm FPA detector 640 x 512
• FOV (continuous zoom)	
- Narrow	2.5° x 2°
- Wide	17.5° x 14°
- Electronic zoom	X3

Day Channel

• Color TV camera	1/4" CCD detector
• FOV (continuous zoom)	
- Narrow	1.7° X 1.2°
- Wide	42° x 32°
- Electronic zoom	X12

Laser

• Laser target illuminator	830 nm (NVG compatible)
• Eyesafe laser range finder (ELRF)	
- Laser wavelength	1.54µm
- Repetition rate	20 ppm continuously
• Laser designator (optional)	

External Interface

- RS 232/422, ETHERNET

Elbit Systems Ltd.
E-mail: istar@elbitsystems.com www.elbitsystems.com

Follow us on

The logo brand, product, service, and process names appearing herein are the trademarks or service marks of Elbit Systems Ltd., its affiliated companies or, where applicable, of other respective holders. All information in this document is for general information only, and is subject for change without notice. © 2016. This brochure contains Elbit Systems and others proprietary information.